



## 10Gb USB 3.2 Gen 2 Switch

### Description

The SW12USB is a USB 3.2 Gen2 10Gb switcher, supporting 4 x USB devices that can be switched to 2 x USB-C host connections.

The SW12USB supports auto switching between host devices using signal sense, or manually controlled via the front-panel push buttons, Web-GUI, TCP/IP, or RS-232



### Key Features

- USB 3.2 Gen2 switch allowing up to 4 x USB peripheral devices to connect to 2 x USB hosts
- Features 2 x USB-C and 2 x USB-A device inputs and 2 x USB-C hosts
- USB 3.2 Gen2 connectivity with data transfer rate up to 10Gbps
- Backwards compatible with USB 2.0 and 1.1
- Auto or manual switching
- Plug-and-play with no drivers, downloads, or software required
- Features 1 x GPI port for integration with 3rd party products
- Features 802.3at PoE+ for powering of product from PoE+ network
- Local 24v power supply input for when network switch does not support PoE+
- Web interface module for control and configuration of SW12USB
- Control via front panel buttons, RS-232, or TCP/IP

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.



## Specifications

- Dimensions (W x D x H): 150mm x 110mm x 23mm
- Shipping Weight: 0.6kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)
- Power Supply: 24V/1.25A DC, 4-pin DIN connector

## Connectivity

- USB Device: 2 x USB Type A female, 2 x USB Type C female
- USB Host: 2 x USB Type C female
- GPI / RS-232 Serial Port: 1 x 4-pin Phoenix connector
- TCP/IP Control: 1 x RJ45, female
- Firmware Upgrade: 1 x Micro-USB

## Package Contents

- 1 x SW12USB
- 1 x 24V/1.25A DC Power Supply
- 1 x Quick Reference Guide
- 1 x Mounting Kit

## Regulatory Compliance



Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.