



Specifications - HMXL44ARC Matrix

- Video Input Connectors: 4 x HDMI Type A, 19-pin, female
- Video Output Connectors: 1 x HDMI Type A, 19-pin, female, 4 x HDBaseT™ RJ45 connectors
- Audio Input Connectors: 1 x Analogue audio L/R (3.5mm stereo Jack), 1 x Optical (S/PDIF)
- Audio Output Connectors: 4 x Analogue audio L/R (3.5mm stereo Jack), 4 x Optical (S/PDIF)
- RS-232 Serial Port: 5 x 3-pin Phoenix connector
- IR Input Ports: 5 x 3.5mm stereo jack
- IR Output Ports: 5 x 3.5mm mono jack
- Rack Mountable: 1U rack height, rack ears included
- Casing Dimensions (W x H x D): 436mm x 43mm x 300mm (without feet)

Specifications - HMXL44ARC-KIT

- Shipping Weight: 3.35kg
- Operating Temperature: 23°F to 122°F (-5°C to +50°C)
- Storage Temperature: -13°F to 158°F (-25°C to +70°C)
- Power Supply (HMXL44ARC): Internal 100-240V AC
- Power Supply (RX70CS): 12V/1A DC, screw type connector (not included)
- HDBT Power Output: 24V DC 0.75A per port

Specifications - RX70CS Receiver

- Video Input Connectors: 1 x HDBaseT™ RJ45 connector
- Video Output Connectors: 1 x HDMI Type A, female
- RS232 Input Port: 1 x 3-pin Phoenix connector
- IR Input Port: 1 x 3.5mm stereo jack
- IR Output Port: 1 x 3.5mm mono jack
- Mounting Kit included
- Casing Dimensions (W x H x D): 140 x 84 x 18mm
- Dimensions Including Connections (W x H x D): 140 x 98 x 18mm

Included Accessories

Receivers	4 x RX70CS
Mounts	4 x Receiver Bracket Sets 1 x Rack Mounting Kit
Controller	1 x Remote Control
Cables	4 x IR Emitters 5 x IR Receivers 1 x Serial Cable - DB9 to 3-pin Phoenix 1 x IR Control Cable IEC Power Cable(s)

Regulatory Compliance



Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.